



OAK[®] PENETRATING OIL

SOLVENT-BASED CORROSION PREVENTIVE OIL

APPLICATIONS	<p>OAK Penetrating Oil is a combination Rust Preventative, Moisture Sealant, Cleaner and Penetrating Lubricant in one product. It frees frozen corroded parts easily and rapidly by absorption on to the metal surface.</p> <p>OAK Penetrating Oil is ideal for both ferrous and non-ferrous metals.</p> <ul style="list-style-type: none">• Loosens frozen pipe joints, nuts, bolts, screws and clamps• Lubricates and stops squeaking hinges, slide mechanisms, precision instruments and gauges, as well as under the hood and external automotive parts• Inhibits corrosion on machine surfaces, bushings, tool room parts and any metal area susceptible to corrosion• Displaces moisture from motors, pumps, switches and wires• Cleans off light soils from machine beds, chucks, ways, gears and internal machine parts
COMPETITIVE ADVANTAGES	<ul style="list-style-type: none">• Loosens frozen metal parts• Wets out metal surfaces, sealing and rust proofing crevices, corners and other hard-to-get-at areas• Excellent long-term indoor rust protection• Displaces water and loosens rust from metal surfaces• Leaves a residual lubricating film when metal expands or contracts• Easily cleanable with either solvent or light-duty alkaline cleaners• Fast drying formulation requires no mixing or measuring

<p>GETTING STARTED</p>	<p>FOR INDUSTRIAL USE ONLY</p> <p>OAK Penetrating Oil is used as received. Can be applied through immersion, brushing, rolling, spraying etc.</p> <p>Can be removed with solvents, alkaline cleaner or degreaser, for subsequent operations.</p> <p>Add no other substances to the concentrate unless approved by your OAK Representative.</p>
<p>TYPICAL PHYSICAL AND CHEMICAL PROPERTIES</p>	<p>Physical state: Liquid Appearance and odor: Clear, solvent Color available: Undyed (light amber) Solubility in water: Insoluble Weight, lb/gal, 60°F (15.6°C): 6.7 Specific gravity, (H₂O = 1): 0.8 Flash point, TCC, °F (°C): 124 (51.1) Extinguishing media: CO₂, foam, dry chemical Unusual fire & explosion hazards: See flash point Freezing point (or pour point), °F, (°C): Not determined. If product freezes, thoroughly thaw and stir before use. Total chlorine, wt%, calculated: 0.00 Silicones: None Residual film: Thin, oily</p>
<p>PACKAGING</p>	<p>Available in 1-gallon cans, 5-gallon pails, 55-gallon drums.</p>
<p>For additional information concerning OAK Penetrating Oil, refer to its OSHA MSDS or contact OAK INTERNATIONAL at 1-269-651-9790.</p> <p>WARRANTY: Oak International, Inc. will grant credit on any product which proves defective in material or workmanship as determined by us subject to the following conditions: all material is subject to our inspection prior to issuing credit; any refund will be adjusted based on the volume of product used; no credit will be granted for used or unused product(s) over one year old as determined by the batch number. The terms in this warranty do not in any way extend to any product thereof covered by this agreement, which has a life, under normal usage, inherently shorter than the one year period indicated above. Except as set forth expressly in writing herein, there are no other warranties express or implied in respect of any product. No warranty of merchantability or fitness for purpose shall apply.</p> <p>LIMITATION OF LIABILITY: Under no circumstances shall we or any affiliate of ours have any liability whatsoever for loss of use or for any indirect or consequential damages.</p> <p>Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet. 12/12/07 REV</p>	

Oak International, Inc., 1160 White St., Sturgis, MI 49091
Ph. 269-651-9790 Fax 269-651-7849 www.oakinternational.com